

	revisions								
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED				
1		RELEASED FOR PRODUCTION.	7/14/2017	DPD	JAG				





												_
ASSY QTY	ASSY QTY	ASSY QTY	ASSY QTY	ASSY QTY	В/О	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.	
				Х		-1	1	SUPPORT ASSEMBLY			2	
			Χ	1		-3		SUPPORT WELDMENT			3	
			1			-5		SUPPORT BLOCK	4140/4142		4	
			1			-7		SUPPORT PLATE	A36/1018/1020 HR		5	
				1		-9		SUPPORT GUIDE BUSHING	4140/4142		6	NOTE:
		Χ				-11	1	PLUNGER ASSEMBLY			7	REF. AIR
		1				-13		PLUNGER BASE	4140/4142		8	KEF. AIK
						-15	1	SUPPORT DISK	4140/4142		9	
						-17	1	PUSHER	4140/4142		10	
						-19	1	INTERMEDIATE BEARING RING	4140/4142		11	
	Χ					-21	1	13mm GAUGE BLOCK ASSEMBLY			12	TITLE
	1					-23		13mm GAUGE BLOCK	4140/4142		13	
Χ						-25	1	20.65mm GAUGE BLOCK ASSEMBLY			14	DWG NO.
1						-27		20.65mm GAUGE BLOCK	4140/4142		15	
						-29	1	CONTENTS PLACARD			16	MAT'L
						-31	1	INSTRUCTION CARD	LAMINATED PAPER		17	HEAT TREAT
		1			B/O	-33		PLUNGER ROD	STEEL	Ø5mm X 30mm (MCMASTER-CARR #91595A372)	7	FINISH
1	1				B/O	-35		GAUGE BLOCK PIN	STEEL	Ø2mm X 14mm (MCMASTER-CARR #91595A030)	12, 14	SPEC
					B/O	-37	1	воттом гоам	ETHAFOAM 220, BLACK	2.97 X 5.93 X 8.43 (CASE SOLUTIONS)	18	DRAWN BY:
					B/O	-39	1	TOP FOAM	ETHAFOAM 220, BLACK	.72 X 5.93 X 8.43 (CASE SOLUTIONS)	19	CHECKED:
					B/O		1	CASE	PLASTIC	PELICAN #APP-1150-E	N/S	OPPS APPR:
					B/O		1	DART PLACARD	ALUMINUM	RB41011	N/S	QA APPR:
ASSY	Υ22Δ	Δ22Υ	ASSY	ASSY	-, -		+-	DATE DOMES	71207411140141	NOTION 1	14/5	APPROVED:
-25	-21	-11	-3	-1								SCALE

REF. AIRBUS T/N: 105-42121W4.

## PRESSING DEVICE


RBE105-42121W4 MAT'L UNLESS OTHERWISE SPECIFIED


DIMENSIONS ARE IN INCHES
.XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 .X ± .1 ANGLES ±.5° SURFACES = 125 1. BREAK ALL SHARP EDGES .015 x 45° OR .015R DD 06/30/2017 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009

REV

HECKED: RJC 07/06/2017 OPPS APPR: AA 07/10/2017 QA APPR: JL 07/10/2017 USED ON MODEL APPROVED: JAG 07/20/2017 EC145, EC645, BO105, BK117 SCALE 6/30/2017 SHEET 1 OF 19 1:4

		REVISIONS			
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED







PRESSING DEVICE

DWG NO. RBE105-42121W4-1

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

.XXX ± .005 FRACTIONS ± 1/8


.XX + .01 ANGLES ±.5°


X ± .1 SURFACES = 125/ TREAT
FINISH ZINC PLATE SPEC ASTM B633 TYPE I SC 2 1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 DRAWN BY: DD 06/30/2017 CHECKED: RJC 07/06/2017 OPPS APPR: AA 07/10/2017 USED ON MODEL JL 07/10/2017


REV

QA APPR: APPROVED: EC145, EC645, BO105, BK117 JAG 07/20/2017 SCALE 6/30/2017 SHEET 2 OF 19

SUPPORT ASSEMBLY








REVISIONS This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR. ECR DESCRIPTION DATE INITIAL APPROVED - .275 - $\phi^{.2019}_{.2001}$  THRU ALL (S.F. -31) Ø.3139 .3135 (P.F. -3)

.03 X 45°-





-106

30°



	REVISIONS							
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED			







PRESSING DEVICE

DWG NO. RBE105-42121W4-11

MAT'L


TREAT
FINISH ZINC PLATE SURFACES = 125/ SPEC ASTM B633 TYPE I SC 2 1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 DRAWN BY: DD 06/30/2017 CHECKED: RJC 07/06/2017 OPPS APPR: AA 07/10/2017 QA APPR: USED ON MODEL JL 07/10/2017


REV

UNLESS OTHERWISE SPECIFIED

APPROVED: JAG 07/20/2017 EC145, EC645, BO105, BK117 SCALE 2:1 6/30/2017 SHEET 7 OF 19

PLUNGER ASSEMBLY





REVISIONS This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR. DESCRIPTION INITIAL APPROVED ECR DATE .645 Ø1.00±.03 Ø.546 **ENGRAVE P/N-**(S.F. -23 & -27) .090 .080 -.08 X 45° 2X .04 X 45°-



DWG NO.

RBE105-42121W4-17

MAT'L 4140/4142 UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

.XXX ± .005 FRACTIONS ± 1/8

.XX + .01 ANGLES ± .5°

.X ± .1 SURFACES = 125/ TREAT
FINISH ZINC PLATE SPEC ASTM B633 TYPE I SC 2 DRAWN BY: DD 06/30/2017 CHECKED: RJC 07/06/2017 OPPS APPR: AA 07/10/2017

1. BREAK ALL SHARP EDGES .015 x 45 'OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009

QA APPR: JL 07/10/2017 USED ON MODEL APPROVED: JAG 07/20/2017 EC145, EC645, BO105, BK117 SCALE 1:1

6/30/2017


**SHEET 10 OF 19** 

REV





MED KNURL

**PUSHER** 



	revisións						
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED		







	DART								
TITLE	PRE	SSINC	DEVI	ICE					
DWG NO.	RBE	105-42	2121W4	4-21	REV 1				
HEAT TREAT FINISH ZINC F	TREAT			UNLESS OTHERWISE SPECIFIED  DIMENSIONS ARE IN INCHES  .XXX ± .005 FRACTIONS ± 1/8  .XX ± .01 ANGLES ± .5°  .X ± .1 SURFACES = 125/					
SPEC ASTM	B633 TYPE		1. BREAK ALL SHARP EDGES .015 x 45° OR .015R						
CHECKED: OPPS APPR:	DD 06/30 RJC 07/0 AA 07/10	6/2017	2. DIMENSION AFTER PLA 3. INTERPRETASME Y14.						
QA APPR:	QA APPR: JL 07/10/2017			USED ON MODEL					
APPROVED:	JAG 07/2	0/2017	EC145, E	C645, BO105, E	3K117				
SCALE	2:1	DATE 6/3	30/2017	SHEET 12 OF	19				


(-21

13mm GAUGE BLOCK ASSEMBLY

		REVISIONS			
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED









## TITLE PRESSING DEVICE DWG NO. REV RBE105-42121W4-23 MAT'L 4140/4142 UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX + .01 ANGLES ± .5° .X ± .1 SURFACES = 125/ HEAT RC 28-32 TREAT RC 28-32 FINISH SEE -21 SPEC 1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 DRAWN BY: DD 06/30/2017 CHECKED: RJC 07/06/2017 OPPS APPR: AA 07/10/2017 QA APPR: JL 07/10/2017 USED ON MODEL APPROVED: JAG 07/20/2017 EC145, EC645, BO105, BK117 SCALE 4:1 6/30/2017 SHEET 13 OF 19

		REVISIONS REVISIONS			
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED







	DART								
TITLE	PRE	SSINC	DEVI	ICE					
DWG NO.	RBE	105-42	2121W4	4-25	REV 1				
MAT'L HEAT TREAT FINISH ZINC F	HEAT TREAT			UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ±.5° .X ± .1 SURFACES = 125/					
SPEC ASTM	B633 TYPE		1. BREAK AL .015 x 45° C	<b>V</b>					
CHECKED: OPPS APPR:	DD 06/30 RJC 07/0 AA 07/10	6/2017	2. DIMENSION AFTER PLA 3. INTERPRE ASME Y14.						
QA APPR:	QA APPR: JL 07/10/2017			USED ON MODEL					
APPROVED:	JAG 07/2	0/2017	EC145, E	C645, BO105, I	3K117				
SCALE	2:1	DATE 6/3	30/2017	SHEET 14 OF	19				


(-25

20.65mm GAUGE BLOCK ASSEMBLY

		REVISIONS			
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED









20.65mm GAUGE BLOCK






 REVISIONS

 REV
 ECR
 DESCRIPTION
 DATE
 INITIAL
 APPROVED





NOTE: USE PDF.

## TITLE PRESSING DEVICE DWG NO. REV RBE105-42121W4-31 MAT'L LAMINATED PAPER UNLESS OTHERWISE SPECIFIED SURFACES = 125/ SPEC 1. BREAK ALL SHARP EDGES .015 x 45 'OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 DRAWN BY: DD 06/30/2017 CHECKED: RJC 07/06/2017 OPPS APPR: AA 07/10/2017 QA APPR: JL 07/10/2017 USED ON MODEL APPROVED: JAG 07/20/2017 DATE 06/30/2017 SCALE **SHEET 17 OF 19**

(-31

INSTRUCTION CARD

